




20W CIRCULAR SOLAR PANEL



FRONT VIEW



SIDE VIEW



BACK VIEW

ELECTRICAL CHARACTERISTICS

Power	20W $\pm 5\%$
Operating Voltage	18V $\pm 5\%$
Operating Current	1.11A $\pm 5\%$
Type of solar cell	Monocrystalline Silicon
STC: Irradiance 1000W/m ² , Module temperature: 25°C, AM=1.5	

TEMPERATURE COEFFICIENTS

Nominal Operating Cell Temperature (NOCT): 45°C $\pm 2^\circ\text{C}$	
Temp. Coefficient of I _{sc}	(0.045 $\pm$ 0.01)%/°C
Temp. Coefficient of V _{oc}	-(0.34 $\pm$ 0.01)/°C
Temp. Coefficient of Power	-(0.47 $\pm$ 0.05)%/°C

TESTED OPERATING CONDITIONS

Max load	50psf 245kg/m ² (2400)pascals
Hailstone impact	25mm(1inch) at 23m/s(52mph)
Temperature	-40° C to + 85° C

MECHANICAL SPECIFICATIONS

Dimensions	Ø500mm, Thickness: 5.5mm
Encapsulation	Glass/EVA/Cells/EVA/TPT
Front Glass	Tempered Glass, thickness: 3.2mm
Frame	Without frame, Solder wire, 800mm long
Efficiency	$\geq 16\%$

FIGURE OF STRUCTURE



WARRANTIES

Power output more than 90% for 10years

The technical files provided by CHINA SOLAR LTD

Office Address:
N0.601, ZhongKang Pioneer Park, ZhongKang Road,
Futian District, ShenZhen City, Guangdong Province, China
Factory Address:
Longxi Hi-tech Industrial Park, Longcheng Road, Longgang
Town, ShenZhen City, Guangdong Province, China



Tel: +86.755.8351 5659
Fax: +86.755.8271 6024
Website: <http://www.solars-china.com>
Email: market@solars-china.com
MSN: market@solars-china.com
Skype: KAXIDY